

MV23

Marathon created MV23 for fleet operators looking for a standard quality friction material to use on applications like liquid tanker, grain, cement or standard duty refuse, as well as general over-the-road hauling. MV23 delivers dependable stopping power with excellent wear characteristics and is a formulation that easily meets Federal regulations in accordance with FMVSS 121 test procedure and is rated for 23,000 lb axle loads.

MV23 linings feature the Hi-Density Marathon formulation (detailed at right) that will improve your bottom line through better performance and fewer maintenance headaches.

MV23 Delivers


- Ideal for general freight hauling and most 23,000 lb. GAWR applications
- Hi-Density formulation for effective heat dissipation
- Excellent brake fade and recovery characteristics
- Dependable stopping performance
- Extremely drum friendly


Hi-Density Friction

One of the most significant design characteristics of any heavy duty brake lining is its density. When higher quality and heavier raw materials are used in a lining's formulation, it creates a higher mass in the block or stated another way, higher density. Truck brakes are designed to convert the energy of a moving vehicle into heat energy. A higher density increases the lining's ability to efficiently handle heat, and is the most critical component in a friction material's fade, recovery and wear.


- Higher density friction materials have the ability to hold more heat energy and therefore more efficiently dissipate the heat
- Higher density friction materials have stronger structural integrity, making them less likely to crack in service, while riveting or due to rust jacking
- Higher density linings exhibit significantly better wear characteristics, especially at higher temperatures
- Higher density friction materials are more resistant to brake fade and water fade

FMVSS 121 Test Results





Fade



Recovery

Testing conducted in accordance with F.M.V.S.S. #121 criteria @ 23,000# axle load: 16 1/2 x 7" S-cam air brake; 30 x 5.5 input power; and a 19.6" tire rolling radius. Shaded area indicates non-compliance.

RSD
APPROVED PER RPO200
ISO 9001
ISO 14001



tip the scale vs. leading competitor

The Marathon Advantage...

See the difference...

higher density

Marathon linings

The Marathon Advantage...
Feel the Difference



125 Old Mill Road • Cartersville, GA 30120 USA

Call 800.223.5201 or visit

MarathonBrake.com